

ITO coated PET film without adhesive

Box No.	Model	Width (mm)	Length(m)	Square (m ²)	Thickness (μm)	Resistance	Haze
1-1.	Oike KA500PS1-175	510	90	45.9	175	450	Clear
1-2.	Oike KA500PS1-175	510	85	43.35	175	450	Clear
1-3.	Oike KA500PS1-175	510	17	8.67	175	450	Clear
1-4.	Oike KA500PS1-175	510	85	43.35	175	450	Clear
1-5.	Oike KA500PS1-175	510	80	40.8	175	450	Clear
1-6.	Oike KA500PS1-175	510	75	38.25	175	450	Clear
1-7.	Oike KA500PS1-175	510	85	43.35	175	450	Clear
1-8.	Oike KA500PS1-175	510	34	17.34	175	450	Clear
2-1.	Oike KA500PS1-188	510	80	40.8	188	450	Anti Glare
2-2.	Oike KA500PS1-188	510	35	17.85	188	450	Anti Glare
2-3.	Oike KA500PS1-188	510	80	40.8	188	450	Anti Glare
3-1.	ITO_AG-240	395	110	43.45	240	ITO coated	Anti Glare
3-2.	ITO_AG-240	395	110	43.45	240	ITO coated	Anti Glare
3-3.	ITO_AG-240	395	111	43.845	240	ITO coated	Anti Glare
3-4.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-5.	ITO_AG-240	395	99	39.105	240	ITO coated	Anti Glare
3-6.	ITO_AG-240	395	110	43.45	240	ITO coated	Anti Glare
3-7.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-8.	ITO_AG-240	395	105	41.475	240	ITO coated	Anti Glare
3-9.	ITO_AG-240	395	101	39.895	240	ITO coated	Anti Glare
3-10.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-11.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-12.	ITO_AG-240	395	105	41.475	240	ITO coated	Anti Glare
3-13.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-14.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-15.	ITO_AG-240	395	111	43.845	240	ITO coated	Anti Glare
3-16.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-17.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-18.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-19.	ITO_AG-240	395	110	43.45	240	ITO coated	Anti Glare
3-20.	ITO_AG-240	395	100	39.5	240	ITO coated	Anti Glare
3-21.	ITO_AG-240	395	105	41.475	240	ITO coated	Anti Glare
4-1.	ITO_clear-240	395	120	47.4	240	ITO coated	Clear
4-2.	ITO_clear-240	395	120.5	47.5975	240	ITO coated	Clear
4-3.	ITO_clear-240	395	121.5	47.9925	240	ITO coated	Clear
4-4.	ITO_clear-240	395	120	47.4	240	ITO coated	Clear
4-5.	ITO_clear-240	395	120	47.4	240	ITO coated	Clear
4-6.	ITO_clear-240	395	120	47.4	240	ITO coated	Clear
4-7.	ITO_clear-240	395	120	47.4	240	ITO coated	Clear

4-8.	ITO_clear-240	395	120	47.4	240	ITO coated	Clear
5-1.	JW TUJ-0300-AG	380	110	41.8	188	300	6.1%
5-2.	JW TUJ-0300-AG	380	110	41.8	188	300	6.1%
5-3.	JW TUJ-0300-AG	380	98	37.24	188	300	6.1%
5-4.	JW TUJ-0300-AG	380	97	36.86	188	300	6.1%
5-5.	JW TUJ-0300-AG	380	112	42.56	188	300	6.1%
5-6.	JW TUJ-0300-AG	380	98.5	37.43	188	300	6.1%
5-7.	JW TUJ-0300-AG	380	98	37.24	188	300	6.1%
5-8.	JW TUJ-0300-AG	380	97	36.86	188	300	6.1%
5-9.	JW TUJ-0300-AG	380	100	38	188	300	6.1%
5-10.	JW TUJ-0300-AG	380	111.5	42.37	188	300	6.1%
5-11.	JW TUJ-0300-AG	380	115	43.7	188	300	6.1%
5-12.	JW TUJ-0300-AG	380	98.5	37.43	188	300	6.1%
5-13.	JW TUJ-0300-AG	380	111	42.18	188	300	6.1%
5-14.	JW TUJ-0300-AG	380	97.5	37.05	188	300	6.1%
5-15.	JW TUJ-0300-AG	380	97	36.86	188	300	6.1%
5-16.	JW TUJ-0300-AG	380	97	36.86	188	300	6.1%
5-17.	JW TUJ-0300-AG	380	100	38	188	300	6.1%
6-1.	JW TUJ-0400-AC	450	97	43.65	188	400	0.6%
6-2.	JW TUJ-0400-AC	450	98.5	44.325	188	400	0.6%
6-3.	JW TUJ-0400-AC	450	35	15.75	188	400	0.6%
7-1.	188-AGAC NAC-400-10	500	52	26	188	ITO coated	Anti Glare
7-2.	188-AGAC NAC-400-10	500	89	44.5	188	ITO coated	Anti Glare
7-3.	188-AGAC NAC-400-10	500	85	42.5	188	ITO coated	Anti Glare
8-1.	Nitto Denko G400L-TFMP	500	70	35	180	400	clear
8-2.	Nitto Denko G400L-TFMP	500	77	38.5	180	400	clear
9-1.	Nitto Denko V270L-TFMP	500	142	71	180	400	clear

Overall square meter

2707.28

- note

This is old inventory. Box condition is not perfect.

Haze for Anti glare is about 6%, and clear is about 1%

Please contact Ashton KIM for further information.

Ashton@FresnelFactory.com